

Attachment Having Clean Copy of Amended Matter

IN THE SPECIFICATION

At page 3, the paragraph beginning at line 17 is amended as follows:

B1 5 According to one embodiment of the invention, the resilient biasing member is a torsional spring. For example, the resilient biasing member is a torsional spring selected from the group of torsional springs including a torsional coil spring, a straight bar spring, and any other conventional torsional spring.

IN THE CLAIMS

- B2 10 1. (Once Amended) A tool bracket, comprising:
a holder structured to engage an elongated portion of a tool;
a mounting base joined for relative rotation to the holder; and
a resilient biasing member coupled to each of the holder and the mounting base and being structured to promote rotation between the holder and the mounting base.
- 15 3. (Once Amended) A tool bracket, comprising:
a holder structured to engage an elongated portion of a tool;
a mounting base joined for relative rotation to the holder; and
a torsional spring biasing member coupled to each of the holder and the mounting base and being structured to promote rotation between the holder and the mounting base.
- B3 20 4. (Once Amended) The tool bracket of claim 1 wherein the biasing member is a torsional spring selected from the group of torsional springs comprising a torsional coil spring, and a straight bar spring.

- B4 25 15. (Once Amended) A bracket for securing a tool having an elongated portion, the bracket comprising:
a means for attaching to an external structure;
a means rotatably coupled to the attaching means for securely engaging an elongated portion of a tool; and

a means coupled between the engaging means and the attaching means for resiliently rotationally biasing the engaging means relative to the attaching means.

134 16. (Once Amended) A bracket for securing a tool having an elongated portion, the bracket comprising:

5 a means for attaching to an external structure;

a means rotatably coupled to the attaching means for securely engaging an elongated portion of a tool; and

a resilient biasing means structured to supply a torsional force between the engaging means and the attaching means for resiliently rotationally biasing the engaging means relative to the attaching means.

10

135 18. (Once Amended) The bracket of claim 15 wherein the engaging means includes means for retaining an elongated portion of a tool that is engaged therewith.